

# **SAFETY DATA SHEET**

HERITAGE VELVET MATT

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1. Product identifier Product name HERITAGE VELVET MATT ÷ 1.2. Relevant identified uses of the substance or mixture and uses advised against **Product use** ż Waterborne coating for interior use. 1.3. Details of the supplier of the safety data sheet ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 70 70 www.duluxtrade.co.uk e-mail address of person : duluxtrade.advice@akzonobel.com responsible for this SDS 1.4 Emergency telephone number **Telephone number** : Emergency Telephone : Slough +44 (0) 1753 550000 Version : 1 No previous validation Date of previous issue SECTION 2: Hazards identification 2.1 Classification of the substance or mixture **Product definition** : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. Ingredients of unknown : 0% toxicity : 0% Ingredients of unknown ecotoxicity See Section 11 for more detailed information on health effects and symptoms.

: No signal word.
: No known significant effects or critical hazards.
<ul> <li>P102 - Keep out of reach of children.</li> <li>P101 - If medical advice is needed, have product container or label at hand.</li> </ul>

## **SECTION 2: Hazards identification**

Prevention	: P262 - Do not get in eyes, on skin, or on clothing.
Response	: P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
Supplemental label elements	<ul> <li>Contains C(M)IT/MIT(3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.</li> <li>Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</li> </ul>
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

#### 2.3 Other hazards

Other hazards which do : None known. not result in classification

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture			
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0,05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1)	[1]
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0,0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the

concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### <u>Туре</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

4.1 Description of first aid measures						
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.					
Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>					
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.					
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.</li> </ul>					
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.					
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.					

## 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray.
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising f	ron	the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	1	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

6.1 Personal precautions, pro	6.1 Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	void breathing vapour or mist. Refer to protective measures nd 8.	listed in sections 7			
For emergency responders	specialised clothing is required to deal with the spillage, tak formation in Section 8 on suitable and unsuitable materials. formation in "For non-emergency personnel".	2			
6.2 Environmental precautions	o not allow to enter drains or watercourses. If the product covers, or sewers, inform the appropriate authorities in accordagulations.				
6.3 Methods and material for containment and cleaning up	contain and collect spillage with non-combustible, absorbent arth, vermiculite or diatomaceous earth and place in contain ccording to local regulations (see Section 13). Preferably cle void using solvents.	er for disposal			
6.4 Reference to other sections	ee Section 1 for emergency contact information. ee Section 8 for information on appropriate personal protect ee Section 13 for additional waste treatment information.	ive equipment.			

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling
Avoid contact with skin and eyes. Avoid inhalation of vapour, spray or mist. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## 7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific : Not available. solutions

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

## 8.1 Control parameters

**Occupational exposure limits** 

No exposure limit value known.

## SECTION 8: Exposure controls/personal protection

Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs/DMELs No DNELs/DMELs available.	
PNECs	
No PNECs available	
8.2 Exposure controls	
Appropriate engineering : controls	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
Individual protection measure	<u>s</u>
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	
Gloves :	When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness $\ge 0.38$ mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness $\ge 0.12$ mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Padu protocijon	The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Body protection :	Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
Other skin protection :	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection :	If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
	OLD LEAD-BASED PAINTS:
	When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

## **SECTION 8: Exposure controls/personal protection**

Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

Respiratory protection in case of dust or spray mist formation. (particle filter EN143 type P2) Respiratory protection in case of vapour formation. (half mask with combination filter A2-P2 til concentrations of 0,5 Vol%.)

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Avoid the inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. OLD LEAD-BASED PAINTS:

When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

Respiratory protection in case of dust or spray mist formation. (particle filter EN143 type P2) Respiratory protection in case of vapour formation. (half mask with combination filter A2-P2 til concentrations of 0,5 Vol%.)

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for

#### HERITAGE VELVET MATT

## **SECTION 8: Exposure controls/personal protection**

lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Avoid the inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Environmental exposure	: Do not allow to enter drains or watercourses.
controls	

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physica	al a	and chemical properties
Appearance		
Physical state	1	Liquid.
Colour	1	Various: See label.
Odour	1	Not available.
Odour threshold	1	Not available.
рН	1	Not available.
Melting point/freezing point	1	Not available.
Initial boiling point and boiling range	1	100°C
Flash point	1	Not applicable.
Evaporation rate	4	Not available.
Upper/lower flammability or explosive limits	1	Not available.
Vapour pressure	1	Not available.
Vapour density	:	Not available.
Relative density	:	1,339
Solubility(ies)	1	Easily soluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Viscosity	1	Kinematic (room temperature): 5,24 cm <sup>2</sup> /s
Explosive properties	1	Not available.
Oxidising properties	1	Not available.
9.2. Other information		
Solubility in water	1	Not available.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity	÷	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.

HERITAGE VELVET MATT

## **SECTION 10: Stability and reactivity**

10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
	LD50 Oral LD50 Oral LD50 Oral		60 mg/kg 53 mg/kg 53 mg/kg	-

**Conclusion/Summary** : Not available.

## Acute toxicity estimates

Not available.

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5	-
C(M)IT/MIT(3:1)	Skin - Severe irritant	Human	-	Percent 0.01 Percent	-
Conclusion/Summary	: Not available.		•	•	
Sensitisation					
Conclusion/Summary	: Not available.				
Mutagenicity					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
<b>Teratogenicity</b>					
Conclusion/Summary	: Not available.				
Specific target organ toxicity	<u>y (single exposure)</u>				
Not available.					
Specific target organ toxicity	<u>y (repeated exposure)</u>				
Not available.					
Aspiration hazard					
Not available.					
Other information	: Not available.				

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 1,5 mg/l Acute EC50 0,4 mg/l Acute IC50 0,067 mg/l	Daphnia - Daphnia magna Daphnia - Pseudomonas putia Algae - Pseudokirchneriella subcapitata	48 hours 16 hours 72 hours
	Acute LC50 1,3 mg/l	Fish - Ochorhyncus mykiss	96 hours
Conclusion/Summary	: Not available.		•

#### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

#### **12.3 Bioaccumulative potential**

Not available.

12.4 Mobility in soil	
Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB a	assessment
PBT :	Not applicable.
	P: Not available. B: Not available. T: Not available.
vPvB :	Not applicable.
	vP: Not available. vB: Not available.

12.6 Other adverse effects : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	<ul> <li>Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.</li> </ul>
Disposal considerations	<ul> <li>Do not allow to enter drains or watercourses.</li> <li>Dispose of according to all federal, state and local applicable regulations.</li> <li>If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.</li> <li>For further information, contact your local waste authority.</li> </ul>
Packaging	

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	<ul> <li>Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.</li> </ul>	
Type of packaging		European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10*	packaging containing residues of or contaminated by hazardous substances
Special precautions	or liners may	I and its container must be disposed of in a safe way. Empty containers retain some product residues. Avoid dispersal of spilt material and pontact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

# Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.

	ADR	IMDG
14.1 UN number	Not regulated.	Not regulated.
14.2 UN proper shipping name	Not applicable.	Not applicable.
14.3 Transport hazard class(es) Class	Not applicable.	Not applicable.
Subsidiary class	-	-
14.4 Packing group	Not applicable.	Not applicable.
14.5 Environmental hazards		
Marine pollutant	No.	No.
Marine pollutant substances		Not available.
14.6 Special precautions for user	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
HI/Kemler number	Not available.	
Emergency schedules (EmS)		Not applicable.
14.7 Transport in bu according to Annex MARPOL and the IB	ll of	·
Date of issue/Date of	of revision : 17-11-2020	Page: 10/13

HERITAGE VELVET MATT Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport. **Additional** information SECTION 15: Regulatory information 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation **Annex XIV** None of the components are listed, or the component present is below its threshold. Substances of very high concern None of the components are listed, or the component present is below its threshold. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other EU regulations** VOC for Ready-for-Use : Not applicable. Mixture Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. **Seveso Directive** This product is not controlled under the Seveso Directive. **National regulations** International regulations **Chemical Weapon Convention List Schedules I, II & III Chemicals** Not listed. Montreal Protocol (Annexes A, B, C, E) Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed. Rotterdam Convention on Prior Informed Consent (PIC) Not listed. **UNECE Aarhus Protocol on POPs and Heavy Metals** Not listed. **15.2 Chemical safety** : No Chemical Safety Assessment has been carried out. assessment

## SECTION 16: Other information

CEPE code	8	
Indicates information that had been set of the set o	s changed from previously issued version.	
	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative	ο.

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Not classified.		

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

Date of printing	: 17-11-2020	
Skin Sens. 1A, H317		SKIN SENSITISATION - Category 1A
Skin Sens. 1, H317		SKIN SENSITISATION - Category 1
Skin Irrit. 2, H315		SKIN CORROSION/IRRITATION - Category 2
Skin Corr. 1C, H314		SKIN CORROSION/IRRITATION - Category 1C
Eye Dam. 1, H318		SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Aquatic Chronic 1, H410		LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Acute 1, H400		SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Acute Tox. 4, H302		ACUTE TOXICITY (oral) - Category 4
Acute Tox. 3, H301		ACUTE TOXICITY (oral) - Category 3
Acute Tox. 2, H330		ACUTE TOXICITY (inhalation) - Category 2
Acute Tox. 2, H310		ACUTE TOXICITY (dermal) - Category 2

Date of issue/ Date of revision	: 17-11-2020
Date of previous issue	: No previous validation
Version	: 1

#### Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this

HERITAGE VELVET MATT

## **SECTION 16: Other information**

data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands