

## STABILISING PRIMER

AM301

Issued December 2018

NEW VERSION: Can be identified by the barcode: 5010212647967


### PRODUCT DESCRIPTION & USE

**Armstead Trade** Stabilising Primer is a professional quality, clear solvent-based primer, formulated to seal powdery exterior masonry surfaces that can be used with most decorative finishes.

### KEY BENEFITS

- **Seals porous, dry & powdery surfaces**
- **Resists alkali attack**
- **Use with Armstead Trade Masonry finishes**

### PACK SIZES



### COLOUR RANGE

Clear.

### COMPOSITION (NOMINAL)

<b>Pigment:</b>	N/A.
<b>Binder:</b>	Acrylic Copolymer
<b>Solvent:</b>	White Spirit.

### VOLUME SOLIDS

9% (nominal).

### SURFACE PREPARATION

All surfaces should be thoroughly prepared by vigorous scraping and brushing to remove any loose or flaking paint and dirt. A stiff fibre brush will give better results than a wire brush, as any wire that becomes embedded in the wall will rust, and stain the new paint. Treat any existing mould or organic growth with \*Weathershield Multi-Surface Fungicidal Wash. Make good minor defects. Use a sand and cement mix for larger holes and cracks.

**Note:** Do not seal sound new or bare surfaces with stabilising primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

### APPLICATION



Brush or roller. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

### SYSTEM INFORMATION

Shake container vigorously before use. After suitable preparation, the normal recommendation is to apply one coat of **Armstead Trade** Stabilising Primer to powdery surfaces, followed by the appropriate **Armstead Trade** exterior finishing system.

### PRACTICAL COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 10m²/litre.

### DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



**Touch Dry:** 2-4 hours\*  
**Recoat:** 16-24 hours\*

\*These times will be significantly longer in cold damp conditions.

### CLEANING UP



After use, remove as much paint as possible from brushes before cleaning with white spirit.

### TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

### VOC

EU limit value for this product (cat.A/h): 750g/l (2007)/750g/l (2010). This product contains max.749g/l VOC.

**\*Weathershield Multi-Surface Fungicidal Wash** contains: Benzalkonium Chloride. Use biocides safely. Always read the label and product information before use.

VOC Content Very High more than 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

### FURTHER SUPPORT

Online: [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk)  
Email: [armstead.advice@akzonobel.com](mailto:armstead.advice@akzonobel.com)  
Phone: 0333-222-70-70  
Please visit [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk) to download safety sheet SDSAM301



Like us on Facebook



Videos on YouTube



Follow us on Twitter



Download on the App Store