

PATENT KNOTTING

For use on knots and resinous areas prior to painting.

Reduces discolouration of topcoats.

A quality knotting made from Shellac.

Caution: We recommend doing a test area first to ensure compatibility with top coats/paint systems to be used. When using lighter coloured paints or water based paints, we recommend using "White Knotting".



500mle

UN No. 1263

R3

SHAKE WELL

Instructions for use: Ensure all surfaces are sound, clean, dry and free from any contaminants. Sand down thoroughly ready for priming and ensure all dust is removed. Wipe knots with Methylated Spirit prior to applying knotting. Apply one coat of knotting over and around all knots and resinous areas working well in, ensuring all knots are properly seaded. Apply a second coat if required after a minimum of one hour. If knots are exuding excessive resin it is recommended to remove them and make good with wood filler. FOR INTERIOR AND EXTERIOR USE. Drving time one hour.

HEALTH & SAFETY

Highly flammable liquid and vapour. • Causes serious eye irritation. • Keep out of reach of children. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. • Wear protective gloves/protective clothing/eye protection/face protection. • Wash contaminated skin thoroughly after handling. • In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. • Store in a well-ventilated place. Keep cool. • Dispose of contents/container in accordance with national regulations.

Contains: Ethanol, Isopropanol, Butanone.

Very high: VOC content >50%

VOCs (Volatile Organic Compounds) Contribute to atmospheric pollution.

EU limit value for this product (A/h 750 g/l (2007) 750 g/l (2010) This product contains max 614 g/l VOC

St. Ivel Way, Warmley, Bristol BS30 8TY. T: +44 (0) 117 960 0060 F: +44 (0) 117 935 2437 E: sales@barrettine.co.uk www.barrettinePro.co.uk Group Website: www.barrettine.co.uk

