

Satin Finish



DESCRIPTION

Johnstone's Trade Satin finish is a solvent based mid sheen finish, formulated for interior use on wood and metalwork, it provides a hardwearing, washable coating which is easy to use giving long term protection to wood and metal surfaces. For best results, use suitable Johnstone's Trade Professional Undercoat.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Brilliant White and over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Satin.

VOLUME SO	DLID

VULUIVII	-

61%

COVERAGE



Johnstone's Trade Satin Finish will cover approximately 20 square metres per litre depending on the nature and porosity of the surface.

FILM THICKNESS

Wet: 50µm, dry: 31µm.

DRYING TIME



Recoatable after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

CLEANER

Cleaner: White spirit.

VOC CONTENT

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.



KEY PROPERTIES

- · Durable and washable
- Resistant to condensation

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well. Easy to apply by brush or roller.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- · Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

1 Litre, 2.5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.