



Stormshield Self-Cleaning Masonry

DESCRIPTION

Johnstone's Trade Stormshield Self Cleaning Masonry has been formulated using ground breaking nano technology in order to give an extremely smooth and dirt resisting finish. Suitable for application to exterior cement rendering, rough cast, brick and concrete, the coating is highly flexible.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Cement rendering, rough cast, brick and concrete.

COLOUR RANGE

Tintable to a range of colours available in Voice of Colour exterior colours.

FINISH

Matt

VOLUME SOLID

30%

COVERAGE



Johnstone's Trade Stormshield Self Cleaning Masonry will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 30µm

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 12 hours.

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

CLEANER

Thinner: Clean water.

VOC CONTENT

EU Limit Value for this product (Cat A/c):
40 g/l (2010) This product contains
max 15g/l VOC



KEY PROPERTIES

- Unique nano particle technology
- Flexible, dirt resisting, smooth finish
- 15 years life expectancy

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Treat fungal or algal growth with Fungicidal Wash as directed. Seal absorbent surfaces with a coat of Stormshield Self Cleaning Masonry, thinned up to 10% with clean water. Wear a suitable face mask when creating dust. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or long pile roller. Also suitable for application by spray. Do not apply in temperatures below 5°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. [Do not use empty container for storing food.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre, 10 Litre



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.