

DESCRIPTION

Johnstone's Trade Anti Mould Acrylic is an acrylic resin based, mould inhibiting coating which protects against algal and fungal growth and dries to a smooth matt finish. Suitable for use on walls and ceilings in food preparation areas and bathrooms where conditions are conducive to mould growth.

RECOMMENDED USES



In areas where conditions are conducive to mould growth, eg. food preparation areas and bathrooms. Use only in accordance with the directions on the label. For interior and exterior use.

SPECIAL PROPERTIES

Quick drying anti-mould properties, durable and washable.

COLOUR RANGE

Brilliant White, Magnolia and a range of colours via the Johnstone's Tinting System.

FINISH

Matt.

VOLUME SOLID

30%.

COVERAGE



Johnstone's Trade Anti Mould Acrylic will cover approximately 9-11 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 30µm.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 4-6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/i): 140 g/l (2010) This product contains max 3g/l VOC



KEY PROPERTIES

- Mould inhibiting
- Protects against algal & fungal growth
- Smooth matt finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Surfaces contaminated with mould growth should be treated with Johnstone's Trade Sterilisation Wash as directed. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



To avoid risks to man and the environment, comply with the instructions for use. **USE ONLY AS DESCRIBED ON THE LABEL.** Ensure maximum ventilation during application and drying. Do not breathe spray. Wear Respiratory Protection. Stir well before use. Suitable for application by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Johnstone's Trade Anti Mould Acrylic thinned with up to 10% clean water. Do not apply in temperatures below 10°C or externally when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. Do not use empty container for storing food.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre and 5 Litre