

DESCRIPTION

Johnstone's Trade Road Marking Paint is a lead free universal road marking paint suitable for application to asphalt, concrete and brick. Its fade resisting properties and rapid drying make it ideal for use on roads, runways, car parks and sports facilities.

RECOMMENDED USES



Line marking requirements on roads, runways, car parks, sports facilities, factories and warehouses.

SPECIAL PROPERTIES

High build, good coverage and wear resistance. Also has good skid resistance. Rapid drying.

COLOUR RANGE

White and Yellow.

FINISH

Matt.

VOLUME SOLID

50%

COVERAGE



Johnstone's Trade Road Marking Paint will cover approximately 2-3 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 380–440µm, dry: 190–220µm.

DRYING TIME



Touch dry in 10 minutes. Hard dry after 30 minutes. Recoatable after 1 hour.

TRANSPORTATION & STORAGE

To avoid risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME**

THINNER

TC1 Thinner and Cleaner.

VOC CONTENT

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 500g/l VOC.



KEY PROPERTIES

- Good wear resistance
- Slip and water resistant
- Rapid drying

PREPARATION

All surfaces to be painted should be dry and free from dust, salts, grease and other contaminants prior to application. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Not recommended for interior use on large surfaces or in confined spaces. Ensure maximum ventilation during application and drying. Stir thoroughly before use. Apply evenly using a clean, well loaded brush. To ensure correct thickness is achieved, do not attempt to brush out or lay off.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with Johnstone's Trade TC1 Thinner & Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre