

## DESCRIPTION

Johnstone's Trade Vinyl Silk Emulsion is formulated for use on interior walls and ceilings, providing a washable, durable silk finish. In areas subject to frequent condensation (e.g. some kitchens and bathrooms), Johnstone's Trade Acrylic Eggshell is more suitable.

## RECOMMENDED USES

**INTERIOR** Suitable for interior use.



## TYPE OF SUBSTRATE

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Silk.

## VOLUME SOLID

31%

## COVERAGE

**COVERAGE** Johnstone's Trade Vinyl Silk will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface being painted. Strong or contrasting colours may require additional coats.



## FILM THICKNESS

Wet: 91µm, dry: 28µm.

## DRYING TIME

**RECOAT** Touch dry in 1-2 hours. Recoatable after 3-4 hours. Do not apply in temperatures below 10°C or in damp conditions.



## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

## THINNER

Thinner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/b): 100g/l (2010) This product contains max 10g/l VOC



## KEY PROPERTIES

- Durable, washable & fade resisting
- High quality silk finish

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Johnstone's Trade Vinyl Silk thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

1 Litre, 2.5 Litre, 5 Litre, 10 Litre.