



COUNTRY COLOUR

Variety of colours and unsurpassed durability – for all weather conditions!



2101
White



2203
Light Ochre



2204
Ivory



2205 Sun-
flower Yellow



2308
Nordic Red



2310 Cedar/
Redwood



2311
Signal Red



2404
Fir Green



2501
Labrador Blue



2506
Royal Blue



2507
Dove Blue



2606
Medium Brown



2607
Dark Brown



2703
Charcoal



2704
Dusk Grey



2708
Pebble Grey



2716 Anthra-
cite Grey



2735
Light Grey



2742
Traffic Grey



PRODUCT DESCRIPTION

Opaque, at first slightly satin-gloss then satin finish natural oil based for wood in outdoor areas.

Wood tone and grain is covered. The wood structure remains noticeable.

Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weatherproof and UV stable surface does not crack, peel, flake or blister.

No sanding necessary, just simply recoat; no primer is needed. Easy and seamless application. Finish stays workable while coating.

The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

RECOMMENDED USE

Osmo Country Colour is best suited for all wood in outdoor areas where an especially durable coating is required: timber cladding, balconies, windows and window shutters, fences, pergolas, wooden shingles, garden furniture and summer houses, carports etc. Ideal for renewing old microporous finishes and weathered wooden surfaces.

INGREDIENTS

Based on natural plant oils (sunflower oil, soya oil and thistle oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). EU limit value for this product (cat. A/e): 400 g/l VOC (2010). This product contains max. 400 g/l VOC.

Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 1.0-1.35 g/cm³

Viscosity: 20-60s DIN EN ISO 2431/4 mm, viscid

Odour: faint/mild, after drying odourless

Flash point: >60°C acc. DIN EN ISO 2719

STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.



SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%).

Osmo Country Colour is ready to use. Do not thin. Stir well before use.

If possible, please apply the first coat to all sides before installation.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed.

As a general rule, wear a dust mask during sanding works.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

If additional protection against blue stain, rot and insects is desired, pre-treat the wood if possible on all sides with Osmo WR Base Coat.

METHODS OF APPLICATION

With Osmo Flat Brush or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and spread well.

Allow to dry for approx. 10-12 hours under good ventilation.

After drying, apply a second coat – also thinly.

For renovation works, one coat applied to the clean and dry surface is usually sufficient.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME

Approx. 10-12 hours (normal climatic conditions, 23°C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

COVERAGE

1 litre covers approx. 26 m² with one coat.

Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

If surfaces in outdoor areas (e.g. windows, cladding) should have additional protection, apply one top coat of Osmo UV-Protection-Oil Clear (410 without film protection or 420 with film protection) after thoroughly drying. This protects against dirt contamination and extends the life of the finish. For Country Colour White 2101, please use Natural Oil Woodstain White 900.

Country Colour, which has been trusted for over decades, is also available in the colour of your choice. Starting from 2.5 litres per colour tone, available in 186 RAL Classic and 1950 NCS colour tones, as well as with biocidal film protection additives.

Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

2101 White
2203 Light Ochre
2204 Ivory
2205 Sunflower Yellow
2308 Nordic Red
2310 Cedar/Redwood
2311 Signal Red
2404 Fir Green
2501 Labrador Blue
2506 Royal Blue
2507 Dove Blue
2606 Medium Brown
2607 Dark Brown
2703 Charcoal
2704 Dusk Grey
2708 Pebble Grey
2716 Anthracite Grey
2735 Light Grey
2742 Traffic Grey

CAN SIZES

0.75 L; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/17